

Designed in line with the strictest environmental regulations for perfect cleaning results with the lowest possible operational costs, Fibrimatic stands for simplified maintenance.

MODERN F LINE DESIGN FEATURES

The modern F LINE design offers advantages in operational savings, as they can be equipped with all options, including those more exclusive like:







- Energy Still, integrated recovery of distillation vapours in order to reduce energy consumption
- Eco System, distillation sludge drying
- Clean Still, automatic cleaning of still with sludge pump
- Integrated Coalperc, solvent absorption system to reduce perc emission at the end of a cycle



MODEL	F10	F15	F18	F25
CAPACITY	10kg	15kg	18kg	25kg
SOLVENT TANKS	2 x 75lt	2 x 105lt/1 x 120lt	2 x 122lt/1 x 160lt	2 x 160lt/1 x 210lt
EXTRACTION RPM	200/400rpm	200/400rpm	200/400rpm	200/400rpm
FILTER WASH	1	2	2	2
FILTER CARBON	1	1	1	1
SILL CAPACITY	100lt	180lt	180lt	230lt
DIMENSIONS (UNCRATED) WxDxH	101 x 195 x 205cm	171 x 151 x 215cm	195 x 165 x 221cm	212 x 190 x 227cm
ISOLATOR REQUIREMENTS	26 amps (380V)	29 amps (380V)	40 amps (380V)	47 amps (380V)
WATER REQUIREMENT	1 x ¾ inch	1 x ¾ inch	1 x ¾ inch	1 x ¾ inch
AIR REQUIREMENT	1 x ¾ inch	1 x ¾ inch	1 x ¾ inch	1 x ¾ inch

RECOMMENDED FOR: Dry Cleaners, Hotels, Textile Industries and Industrial Laundries

FINISHING, PRESSING AND CONVEYORS



A. LAV/U B. MPT-D C. MG-C D. GE25 E. GFV F. FVC G. CCP H. LAV/F I. SC

